

THERMAL SHRINK PACKING MACHINE
เครื่องอบฟิล์มหดอุณหภูมิ



BSD3520A BSD4020A BSD4525A

BSD Series

FEATURES:

1. Works with all types of shrink films
2. Temperature compensating solid state controllers
3. Belt conveyor with variable speed and adjustable
4. Top & side heat, Stainless-steel heater
5. Quick change seal wire with tension assembly
6. Roller, wire mesh optional
7. High velocity turbo-tunnel
8. Combination unit-system runs on one circuit



Model	BSD3520A	BSD4020A	BSD4525A
Power supply	110,220-240V/50-60Hz 1	110,220-240V/50-60Hz 1	380V/50Hz 3
Heater power	7KW Adjustable	8KW Adjustable	10KW Adjustable
Conveyor speed	0-15m/min	0-15m/min	0-15m/min
Tunnel size	80x35x20cm	100x40x20cm	100x45x25cm
Shrink product size	300x160mm	350x160mm	400x210mm
Conveyor loading	15kg Maximum	25kg Maximum	25kg Maximum
Machine size	105x55x110cm	120x60x115cm	120x69x120cm
Machine weight	75kg	90kg	100kg
Shrink film	POF,PVC, PP	POF,PVC,PP	POF,PVC,PP



BSD3520A BSD4020A BSD4525A

BSD Series