



MASTER WA

Labelling system for wrap around application onto cylindrical flacons.

Standard features

Max. speed up to	12000 p/hour
Labelling module	LABELX 140 ES

Horizontal and vertical microregulation unit with numeric indicators | Conveying module with flat belt | Wrap around device with AC motor plus inverter | Automatic speed synchronization | MASTER main frame in painted steel (Stainless on request) | Centralized electronic control with colour Touch screen operator panel | PLC unit with memory of setting parameters | Total protection in polycarbonate

MASTER TS

Labelling system for application top application onto pharmaceutical boxes

Standard features

Max. speed up to	12000 p/hour
Labelling module	LABELX 140 ES

Horizontal and vertical microregulation unit with numeric indicators | Conveying module with parallele flat belt with pushing bars | Product sperating and synchronizing device | Automatic speed synchronization | MASTER main frame in painted steel (Stainless on request) | Centralized electronic control with colour Touch screen operator panel | PLC unit with memory of setting parameters | Total protection in polycarbonate

ACCESSORIES

Pre-unwinding diameter 500



Camera control



Thermal transfer coder



Inclined planes regulation





Print & apply systems for high performances

Standard features

Electronic unit	PLC
Display	Colour touch screen
Printing unit	4" (105mm) 6" (160mm)
Applicator modules	Integrables on demand
Roll holder	300 mm
Rewinder	Motorized

Mechanical unwinder | End of roll alarm

Accessories

Start photocell
Pre-end of roll alarm



SERIES AL
Linear pneumatic applicator.



SERIES AF
Pneumatic applicator with rotating arm.