

PW-551TB AUTO CARTON SEALING MACHINE TOP AND BOTTOM BEIT DRIVE New Yage Head- Potent No. 1738 New Yage Head- Potent No. 1738

- position for consistent sealing of every carton. This design is superior to previous blower devices
- Flexible cushion prevents box been jammed under the top tapping head.
- Tape overlap length can be adjusted from 55~ 65mm.
- Tape overlap of 70±5 or 95±5mm can be provided on request.
- Wider belt-75mm firmly seize the carton, new 1 linking buckle "design allowing the belt to be changed easily.
 Oversized drive rollers guide belt design stops slipping and prolongs belt life.
- Aluminum guide machanism allow tape head bracket to move very stable and smooth.
 Both side guide rails can be adjusted separately to meet the carton width.











PW-552TB AUTO CARTON SEALING MACHINE





 Flexible cusion avoids box riexible cusion avoids box jammed under top tapping head.



Options:



PW-552TB

SPECIFICATIONS : • Of













3	Distributor:
	Distributor.

Model	PW-551TB	PW-552TB
Power supply	1Ø, 110V, 220V (50/60Hz)	1Ø, 110V, 220V (50/60Hz)
	3Ø, 220V, 380V, 440V (50/60Hz)	3Ø, 220V, 380V, 440V (50/60Hz)
	Two motors, 374W	Two motors, 374W
Sealing speed	20M / min at 60Hz	20M / min at 60Hz
Cartons / hr	2400 cartons per hour (60Hz)	2400 cartons per hour (60Hz)
	(carton L300 x W300 x H300mm)	(carton L300 x W300 x H300mm)
Tape width	2" or 3" (2 or 2.5 tape also can be used	2" or 3" (2 or 2.5 tape also can be used
	in 3" tape head with paper roll)	in 3" tape head with paper roll)
Shipping size	L1286 x W836 x H1474 (mm)	L1096 x W836 x H1574 (mm)
	L50.6" x W32.9" x H58"(inch)	L43.1" x W32.9" x H62"(inch)
N.W.	151kgs, 332(lbs)	160kgs, 352(lbs)
G.W.	211kgs, 464(lbs)	220kgs, 484(lbs)