



The only lowest electric current packaging machine in global

TP-999

Automatic Strapping Machine



Characteristics

- III Desk - Top
- III Paper Tape and transparent Plastic Tape are Available for Strapping at Same Machine.
- III Automatic Strapping
- III Microcomputer Controlled for Easy Operator
- III 3 Positions of Tension Control
- III Star Modes
 - (A) Auto Start
 - (B) Start Button
 - (C) Foot Switch

Specification

- III Strapping Capacity : 300mm (W) x 200mm (H)
Strapping Speed : 18 - 20 Cycles/Min
Dimension :
 - a. Without Tape and Holder : 562mm (W) x 318mm (D) x 376mm (H)
 - b. With Tape and Holder : 586mm (W) x 318mm (D) x 480mm (H)Tape width/length : 30mm x 150m Paper Tape or Transparent Plastic
Net Weight : 17.5 Kgs
Power Supply : AC220V, Power Consumption : Max 100W



PT Asia, Thailand Co.,Ltd.
15/648 Moo 10, Samrong Nua, Maung, Samutprakarn 10270 Thailand
tel. +66 2 759 2271, 2964, 0717, 1937
fax. +66 2 380 5265, 759 3569
Email : info@ptasia.biz
Website : <http://www.ptasia.biz>